



C3-100 Pro

➔ C3 100 Pro - 1 Door Access Control

Number of Doors controllers : 1 Door
Number of Readers Supported : 2(26-bit wiegand reader)
Types of Readers Supported : The range of wiegand format: 26 bits to 66 bits
Number of Inputs : 2 (Exit Device and Door Status, AUX)
Number of Outputs : 2 (1-From C Relay for Lock and 1-Form C Relay for Aux Output)
Card Holders Capacity : 100000
Log Events Capacity : 100000 (Optional 200000)
Weight : 7.4lbs (3.35kg)
Communication : TCP/IP, RS-485 and WiFi optional
CPU : 1.2GHZ CPU | RAM : 128MB
Push Data (centralization)
Flash Memory : 256MB
Enclosure : Metal Box
Mounting : Wall Mount
Recommended Power Supply : 12V DC, 2A
Dimensions (Bundle Only) : 15in.×3.15in.×11in
Dimensions (Board Only) : 6.3in.×4.17in
Operating Temp : 0-45 °C
Operating Humidity : 20% to 80%

Features

- 256 time Zones, 256 access levels
- Multi-Card Opening function, Remote door opening and closing
- Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- Real-Time monitoring Via Web browser
- 1 auxiliary input can be connected to infrared body, Detectors, Fire alarms, smoke detectors etc.
- 1 auxiliary output can be connected to alarms, cameras, door bells, light indicator etc.
- Global Anti-pass back, Global Interlock and Global linkage
- Alarms and Events Notifications through Email
- who is inside
- Supports Video Integration & Visitor Management Module

Software and Database Supported:

- Bio Security 3.0 (Web based application)
- PGSql by default, Supported MSSQL 2005/2008/2012 and Oracle 11g enterprise edition.