



ESSL SPEEDFACE-V5

Biometrics & RFID, Time & Attendance + Access control, Face System



Secure Service Plus

Technical Specification High Speed Face Authentication System

Capacity	User capacity	10,000
	Face capacity	6,000 (standard) 10,000 (optional)
	Fingerprint capacity	10,000
	RFID capacity	10,000 (optional)
	Transactions capacity	2,00,000 Logs
Hardware	CPU	Quad-core A17 1.8GH
	Memory	2GB RAM / 16GB ROM
	Display	5inch LCD touch screen
	Camera	2MP dual lens
	Audio	Loudspeaker
	Communication	TCP / IP, RS485
	Access	Door lock, door sensor, alarm
		Exit button and auxiliary input
Power	Operating Voltage	12V 3A
	Temperature	-10 °C ~ 45 °C
	Humidity	10% ~ 90%

Features

6,000 facial users' capacity, maximum 10,000 facial users

ID/MF optional, 5-inch touch LCD

Dual-camera for live face detection, Face recognition distance: 0.3 m to 1 m

Compatible with external RS485 and Wiegand reader

TCP/IP, Wi-Fi communication

High performance processor with deep learning algorithm

Accurate and fast face recognition

Secure Service Plus

No.3, 1827, Sy.No 6/1, near Vijaya Bank, AECS
Layout - A Block, Singasandra, Bangalore,
Karnataka 560068

Sales & Support: +91 99026 70055