



## C3-400 Pro

### ➔ C3 400 Pro - Door Access Control

Number of Doors controllers : 4 Doors  
Number of Readers Supported : 12  
(8 RS-485 Reader OR 4 26-bit wiegand reader)  
Types of Readers Supported : The range of wiegand format: 26 bits to 66 bits  
Number of Inputs : 12 (4 Exit Device, 4 Door Status, 4 AUX)  
Number of Outputs : 8 (4-Form C Relay for Lock and 4-Form C Relay for Aux Output)  
Card Holders Capacity : 100000  
Log Events Capacity : 100000 (Optional 200000)  
Weight : 7.8lbs (3.55kg)  
Communication : TCP/IP, RS-485 and WiFi optional  
CPU : 1.2GHZ CPU | RAM : 128MB  
Push Data (centralization)  
Flash Memory : 256MB  
Enclosure : Metal Box  
Mounting : Wall Mount  
Recommended Power Supply : 12V DC, 5A  
Dimensions (Bundle Only) : 15in.×3.15in.×11in  
Dimensions ( Board Only) : 6.3in.×4.17in  
Operating Temp : 0-45 °C  
Operating Humidity : 20% to 80%

### Features

- 256 time Zones, 256 access levels
- Multi-Card Opening function, Remote door opening and closing
- Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- Real-Time monitoring Via Web browser
- 4 auxiliary inputs cab be connected to infrared body, Detectors, Fire alarms, smoke detectors etc.
- 4 auxiliary outputs can be connected to alarms, cameras, door bells, light indicator etc.
- Global Anti-pass back, Global Interlock and Global Linkage
- Alarms and Events Notifications through Email
- who is inside
- Supports Video Integration & Visitor Management Module.

### Software and Database Supported:

- Bio Security 3.0 (Web based application)
- PGSql by default, Supported MSSQL 2005/2008/2012 and Oracle 11g enterprise edition.